

Safety Data Sheet

MILSPRAY™ MIL-DTL-53039E Type IV - 37030 Black - Single Component
Revision Date: March 10, 2021

Page: 1/7

Contains NCP Coatings DynaSpec Black MIL-DTL-53039E TIV

Section 1 - Manufacturer Identification

Product Name: MIL-DTL-53039E Type VII - 37030
Black - Single Component

Recommend Use: Touch-Up Military Paint

Supplier's Name: MILSPRAY Military Technologies™

Address: 845 Towbin Ave
Lakewood, NJ 08701

Phone: 732-886-2223

EMERGENCY PHONE: 1-800-424-9300 (Chemtrec)



HMIS		NFPA	
Health	2	2	0
Flammability	3	2	0
Reactivity	1	0	0
Personal Protection	G		

Section 2 - Hazards Identification

EMERGENCY OVERVIEW:

Immediate Concerns: Flammable liquid and vapor.

Physical Appearance: Liquid

GHS Ratings:

Flammable Liquid	3
Resp. Sens.	1
Acute Toxicity Inhalation	4
Skin Sensitizer	1
Eye Damage/Irritation	2A
STOT SE	3
STOT RE	2



GHS Signal Word: Danger

GHS Hazards:

Flammable liquid and vapor.
May cause an allergic skin reaction.
Causes serious eye irritation.
Harmful if inhaled.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause respiratory irritation.
May cause damage to organs through prolonged or repeated exposure.

GHS Precautions

IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

If skin irritation or rash occurs: Get medical advice / attention.

If experiencing respiratory symptoms: Get medical advice / attention.

Keep away from heat/sparks/open flames/hot surfaces. — No smoking.

Safety Data Sheet

MILSPRAY™ MIL-DTL-53039E Type IV - 37030 Black - Single Component

Revision Date: March 10, 2021

- Ground/bond container and receiving equipment.
- Use explosion-proof electrical/ventilating/lighting/equipment.
- Avoid breathing dust/fume/gas/mist/vapors/spray.
- Do not get in eyes, on skin, or on clothing.
- Do not eat, drink or smoke when using this product.
- Use only outdoors or in a well-ventilated area.
- Wear protective gloves/protective clothing/eye protection/face protection.
- In case of inadequate ventilation wear respiratory protection.
- Wash contaminated clothing before reuse.
- Dispose of contents/container in accordance with local/national/international regulations.
- In case of fire: Use appropriate method to extinguish. See Section 5 of SDS.
- Store in a well-ventilated place. Keep container tightly closed.
- Store in a well-ventilated place. Keep cool.

Section 3 - Composition/Information on Ingredients

Chemical	Weight Percent	CAS Number
Parachlorobenzotrifluoride	35-40%	98-56-6
Hexamethylene Diisocyanate Homopolymer	10-15%	28182-81-2
Methyl Isoamyl Ketone	1-5%	110-12-3
Carbon Black	1.71%	1333-6-4

*Toxic chemical subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

"WARNING: THIS PRODUCT MAY CONTAIN CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM."

Section 4 - First Aid Measures

EYE CONTACT: Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated shoes and clothes and clean before reuse.

INGESTION: DO NOT induce vomiting. Get medical attention immediately.

INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

Safety Data Sheet

MILSPRAY™ MIL-DTL-53039E Type IV - 37030 Black - Single Component

Revision Date: March 10, 2021

SYMPTOMS: May cause respiratory irritation, dizziness, or drowsiness.

EFFECTS: Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin, and/or eyes. Overexposure and long term exposure to isocyanate can cause lung and skin sensitization.

Section 5 - Fire Fighting Measures

FLASH POINT: 100F (38°C) SETAFLASH CLOSED CUP

LEL: 0.9

UEL: 10.5

SUITABLE EXTINGUISHING MEDIA: Foam, Powders, Carbon Dioxide, or Dry Chemical.

UNSUITABLE EXTINGUISHING MEDIA: Not available.

UNUSUAL FIRE & EXPLOSION HAZARDS: Flammable liquid and vapor. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, grind or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning. Product reacts with water releasing large amounts of carbon dioxide which may cause pressure build up in confined spaces. Toxic vapors and corrosive fumes can be emitted during fire conditions.

PRODUCTS OF COMBUSTION: During combustion toxic vapors may be released. Under fire conditions, corrosive fumes and toxic vapors may be emitted.

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Use water with caution, product will react with water and release large amounts of carbon dioxide which may cause pressure build up in confined spaces. Water spray to cool containers or protect personnel, but avoid direct contact between water and the product. Small fires: carbon dioxide or dry chemical. Large fire: alcohol-type aqueous film-forming foam or dry chemical.

NFPA 704: Health = 1 Flammability = 3 Instability = 0

Section 6 - Accidental Release Measures

PERSONAL PRECAUTIONS: Not available.

ENVIRONMENTAL PRECAUTIONS: Avoid runoff into storm sewers and ditches which lead to waterways.

METHODS OF CONTAINMENT: Dike spill area and absorb the spilled liquid with earth, sawdust or a commercially available absorbent.

METHODS OF CLEAN-UP:

SMALL SPILLS: Eliminate all sources of ignition. Provide good ventilation and minimize the breathing of vapors and avoid skin contact. Dike spill area and absorb the spilled liquid with earth, sawdust or a commercially available absorbent. Shovel spent absorbent into recovery or salvage drums for appropriate disposal.

LARGE SPILLS: Wear appropriate personal protective equipment. Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. Use only non-combustible material for cleanup. Use clean, non-sparking tools to collect absorbed materials. Absorb spill with inert material (e.g. dry sand, earth or sawdust), then place in a chemical waste collector.

OTHER INFORMATION: EMERGENCY PRECAUTIONS: Eliminate ignition sources. Avoid large exposures to vapors.

Section 7 - Handling and Storage

HANDLING: Use only in a well ventilated area. Avoid breathing vapor, fumes, or mist. Avoid contact with eyes, skin, and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Always open containers slowly to allow any excess pressure to vent. Avoid contact with water or humidity. Follow all SDS/label precautions even after containers are emptied because they may retain product

Safety Data Sheet

MILSPRAY™ MIL-DTL-53039E Type IV - 37030 Black - Single Component

Revision Date: March 10, 2021

Page: 4/7

residues.

STORAGE: Keep away from heat, sparks, and flame. Store containers in a cool, well ventilated place. Keep container closed when not in use.

Section 8 - Exposure Controls/Personal Protection

Components	CAS	Limits
Parachlorobenzotrifluoride	98-56-6	ACGIH TLV NE OSHA PEL NE
Hexamethylene Diisocyanate Homopolymer	28182-81-2	OSHA PEL: NE ACGIH TLV: NE
Methyl Isoamyl Ketone	110-12-3	ACGIH TLV: 50 PPM OSHA PEL: 50 PPM
Carbon Black	1333-86-4	OSHA PEL: 3.5 mg/m3 TWA ACGIH TLV: 3.5 mg/m3 TWA

NE=Not Established

ENGINEERING CONTROLS: Engineering controls should be in place to minimize exposure to vapors and any ignition sources.

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

SKIN PROTECTION: Wear impervious gloves to prevent contact with skin. Wear protective gear as needed - apron, suit, boots.

RESPIRATORY PROTECTION: NIOSH/MSHA approved respirators may be necessary if airborne concentrations are expected to exceed exposure limits. In the event of insufficient ventilation, Self-contained breathing apparatus is recommended.

HYGIENE: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

OTHER USE PRECAUTIONS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Section 9 - Physical and Chemical Properties

PHYSICAL STATE: Liquid

ODOR: Typical

ODOR THRESHOLD: Not determined.

pH: Not determined.

BOILING POINT: 144°C

FLASH POINT: 100F (38°C) SETAFLASH CLOSED CUP

FLAMMABILITY LIMITS: 0.9 to 10.5

VAPOR PRESSURE: Not determined.

VAPOR DENSITY: Not determined.

SPECIFIC GRAVITY: 1.2568010

Safety Data Sheet

MILSPRAY™ MIL-DTL-53039E Type IV - 37030 Black - Single Component
Revision Date: March 10, 2021

Page: 5/7

AUTO-IGNITION TEMPERATURE: Not determined.

VOC EPA METHOD 24: 1.0032055 lb/gal

Section 10 - Stability and Reactivity

STABILITY: No information available.

CONDITIONS TO AVOID: Not available.

INCOMPATIBLE MATERIALS: Prevent contact with water and aqueous solutions, alcohols, amines, bases, strong acids, and strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: During thermal decomposition, toxic gasses, corrosive gasses, and nitrogen oxides may be formed.

POSSIBILITY OF HAZARDOUS REACTIONS: No information available.

Section 11 - Toxicological Information

LIKELY ROUTES OF EXPOSURE: Eye contact, Skin contact, Ingestion, and Inhalation

EYE: Can cause eye irritation.

SKIN: Causes skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INHALATION: Vapors are irritating to nasal passages and throat. High concentrations can cause stupor and headaches. May cause respiratory irritation and difficulty breathing. May cause dizziness and drowsiness.

Ingestion: Irritating to mouth, throat, and stomach. May cause headache. May cause dizziness and drowsiness and/or stupor.

CHRONIC EFFECTS: Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin, and/or eyes.

TARGET ORGANS: Not available.

CANCER INFORMATION: Not available.

CARCINOGENICITY: Not available.

DEVELOPMENTAL INFORMATION: Not available.

MIXTURE TOXICITY: Not available.

ACUTE TOXICITY VALUES: The acute effects of this product have not been tested. Data on individual components are listed below.

CAS Number	Test
98-56-6	Oral LD50: 13,000, Dermal LD50: 2,700, Vapor LC50: 33,
28182-81-2	Oral LD0: Rat: >2500 mg/kg), Dermal LD0: Rabbit >2000 mg/kg >2000 mg/kg Rat, Inhalative LC50: .390 mg/l rat 4 h,
110-12-3	Oral LD-50:(Rat):5.657 mg/kg, Dermal LD-50 (Guinea Pig):>10 ml/kg, NOEL (Rat, Oral Study, 90 d): 200 ppm,
1333-86-4	Oral LD50: <8000 mg/kg

Safety Data Sheet

MILSPRAY™ MIL-DTL-53039E Type IV - 37030 Black - Single Component

Revision Date: March 10, 2021

Page: 6/7

Section 12 - Ecological Information

ENVIRONMENTAL EFFECTS: Information not available on mixture. Information on individual components is listed below if available.

CAS Number	Test
98-56-6	No Information available.
28182-81-2	The product does not have any known adverse effects on the aquatic organisms tested.
110-12-3	LC-50 (Fish, 96h): 159 mg/l, EC-50 (Alga, 72 h):>100 mg/l (highest concentration tested), 67% (28 d, Ready Biodegradability: Closed Bottle Test) Readily biodegradable,
1333-86-4	Acute algae EC50:>10,000 mg/L, Acute fish LC50>1000mg/L, Acute water flea EC50;>5600 mg/L

Section 13 - Disposal Considerations

Dispose of waste in accordance with all local, state, and federal regulations.

Section 14 - Transport Information

DOMESTIC (USDOT):

Proper Shipping Name: Paint

Hazard Class: 3

Packing Group: III

Quantity: Not applicable.

UN Number: 1263

Section 15 - Regulatory Information

REGULATORY OVERVIEW: The regulatory data in section 15 is not intended to be all-inclusive, only selected regulations are represented.

TSCA: All components of this material are either listed or exempt from listing on the TSCA Inventory.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT) 311/312/313 REPORTABLE INGREDIENTS: See Section 3.

EPA HAZARDS:

FIRE: Yes

PRESSURE GENERATING: No

REACTIVITY: No

ACUTE: Yes

CHRONIC: Yes

DSL: All components of this material are on or exempt from listing on the Canadian Domestic Substances List (DSL).

Safety Data Sheet

MILSPRAY™ MIL-DTL-53039E Type IV - 37030 Black - Single Component
Revision Date: March 10, 2021

Page: 7/7

Section 16 - Other Information

HMIS: Health = 2 Flammability = 3 Reactivity = 1 Personal Protection = G

NFPA 704: Health = 2 Flammability = 2 Instability = 0

DISCLAIMER:

This SDS is based on information believed to be reliable and accurate. Because of changing reporting requirements and other variables it is impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to determine proper personal protection based on the actual condition of use and to comply with all Federal, State and Local laws and regulations.