MILSPRAY Fed-Std 595B #34094 Non-CARC 1K Aerosol Can Revision Date: October 27, 2015

Contains Custom-Pak U.S. Military FED-STD-595B 34094 GREEN Formula 34A169N6

## **Section 1 - Manufacturer Identification**

Product Name: FED-STD-595B #34094 Green

Non-CARC 1K Aerosol Can

Recommend Use: Touch-Up Military Paint

Supplier's Name: MILSPRAY Military Technologies

Address: 845 Towbin Ave

Lakewood, NJ 08701

**Phone:** 732-886-2223

**EMERGENCY PHONE**: 1-800-424-9300 (Chemtrec)





## **Section 2 - Hazards Identification**

#### **GHS Rating:**

Flammable Aerosols 1 Gases Under Pressure Compressed Liquid Acute Toxicity - Oral 4 **Aspiration Hazard** 1 Acute Toxicity - Dermal 4 Skin Corrosion/Irritation 2 Serious Eye Damage/Irritation 2A Acute Toxicity - Inhalation 4 Specific Target Organ Toxicity

Single Exposure 3
Germ Cell Mutagenicity 1A,1B
Carcinogenicity 1A,1B

Percentage of the mixture consisting of ingredient(s) of unknown toxicity: 17.9%

#### GHS Signal Word: Danger

#### **GHS Hazards:**

Extremely flammable aerosol.

Contains gas under pressure; may explode if heated.

Harmful if swallowed.

May be fatal if swallowed and enters airways.

Harmful in contact with skin.

Causes skin irritation.

Causes serious eye irritation.

Harmful if inhaled.

May cause respiratory irritation.

May cause drowsiness or dizziness.

May cause genetic defects.

May cause cancer.

#### **GHS Precautions:**

Keep out of reach of children.

Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Keep away from heat/sparks/open flames/other ignition sources. No smoking.

Do not spray on an open flame or other ignition source.



MILSPRAY Fed-Std 595B #34094 Non-CARC 1K Aerosol Can Revision Date: October 27, 2015

Pressurized container: Do not pierce or burn, even after use.

Avoid breathing vapor/spray.

Wash hands thoroughly after handling.

Use only outdoors or in a well-ventilated area.

Wear eye protection.

IF SWALLOWED: Immediately call a poison center/doctor.

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: Remove victim to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Call a POISON CENTER/doctor if you feel unwell.

Do NOT induce vomiting.

If eye irritation persists: Get medical advice/attention.

Store in a well-ventilated place. Keep container tightly closed when not in use.

Protect from sunlight. Store in a well-ventilated place.

Protect from sunlight. Do not expose to temperatures exceeding 50 degrees C/122 degrees F.

Dispose of contents/container in accordance with local/regional/national regulations.

# **Section 3 - Composition/Information on Ingredients**

Product Name	CAS#	% by weight
acetone	67-64-1	37.5
propane	74-98-6	16.3
n-butyl acetate	123-86-4	8.4
n-butane	106-97-8	7.7
xylene	1330-20-7	6.8
*ethylbenzene	100-41-4	1.6
PM acetate	108-65-6	1.4
Titanium dioxide	13463-67-7	0.6
ethyl ester	763-69-9	0.5
ethyl acetate	141-78-6	0.4
*carbon black	1333-86-4	0.3
(BIN 14) aliphatic hydrocarbon	8052-41-3	0.2
aliphatic petroleum naphtha	64742-48-9	0.1
Petroleum solvent	64742-47-8	0.1
Isobutyl alcohol	78-83-1	0.1
n-butyl alcohol	71-36-3	0.1

## **Section 4 - First Aid Measures**

**EYE CONTACT**: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

**INHALATION:** If inhaled: Move person to fresh air and keep in comfortable position for breathing. If breathing difficulty persists: Get medical advice/attention.

MILSPRAY Fed-Std 595B #34094 Non-CARC 1K Aerosol Can Revision Date: October 27, 2015

**SKIN CONTACT**: If on skin: Wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. If skin irritation persists: Get medical advice/attention.

Page: 3/6

**INGESTION:** If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting unless directed to do so by medical personnel.

#### MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

See Section 11: Toxicological Information and effects.

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT REQUIRED Treat symptomatically.

# **Section 5 - Fire Fighting Measures**

SUITABLE EXTINGUISHING MEDIA: CO<sub>2</sub> (Carbon Dioxide), dry chemical, or water fog.

**UNSUITABLE EXTINGUISHING MEDIA:** Water spray may be unsuitable. However, if water is used, fog nozzles are preferable. Water may be used to cool closed containers to prevent pressure build-up and possible explosion when exposed to extreme heat.

**SPECIFIC HAZARDS ARISING FROM CHEMICAL:** Closed containers exposed to heat from fire may build pressure and explode. Products of combustion may include but are not limited to: oxides of carbon.

**SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS:** Full protective equipment including self-contained breathing apparatus should be used.

### **Section 6 - Accidental Release Measures**

PERSONAL PRECAUTIONS: Use personal protection recommended in Section 8.

**ENVIRONMENTAL PRECAUTIONS:** Prevent contamination of soil/ground, waterways, drains, and sewers.

**METHODS OF CONTAINMENT:** Absorb spilled liquid in suitable material.

METHODS OF CLEAN-UP: Use spark-proof tools to sweep or scrape up, containerize, and dispose of properly.

**OTHER INFORMATION:** Ensure adequate ventilation.

# **Section 7 - Handling and Storage**

**HANDLING**: Vapors may ignite explosively. Prevent buildup of vapors. Keep from sparks, heat, flame or other heat sources. Do not smoke. Turn off pilot lights, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Do not puncture or incinerate/burn container. Keep container tightly closed while not in use.

**STORAGE:** Store in dry, well-ventilated area and in accordance with federal, state, and local regulations. Do not expose to heat or store at temperatures above 50 degrees C / 122 degrees F. If storing in cold temperatures, allow product to warm to room temperature before use. Keep container tightly closed and away from heat and sunlight when not in use.

# **Section 8 - Exposure Controls/Personal Protection**

Product Name	OSHA PEL-TWA	ACGIH TLV-STEL	ACGIH TLV-TWA
acetone	1000 ppm	750 ppm	500 ppm
propane	1000 ppm	1800 ppm	2500 ppm
xylene	100 ppm	150 ppm	100 ppm
n-butane	800 ppm	N/E	800 ppm
n-butyl acetate	150 ppm	200 ppm	150 ppm
*ethylbenzene	100 ppm	125 ppm	100 ppm
*carbon black	3.5 mg/m ppm	N/E	3.5 mg/m ppm
PM acetate	N/E	N/E	N/E

MILSPRAY Fed-Std 595B #34094 Non-CARC 1K Aerosol Can Revision Date: October 27, 2015

ethyl ester	N/E	100 ppm	50 ppm
(BIN 14) aliphatic hydrocarbon	N/E	N/E	N/E
ethyl acetate	400 ppm	N/E	400 ppm
Isobutyl alcohol	300 ppm	N/E	50 ppm
n-butyl alcohol	300 ppm	N/E	50 ppm
Titanium dioxide	15 mg/m3 ppm	N/E	10 mg/m3 ppm
aliphatic petroleum naphtha	500 ppm	N/E	100 ppm
Petroleum solvent	400 ppm	N/E	N/E

**ENGINEERING CONTROLS:** Provide adequate ventilation to keep air contamination below OSHA permissible exposure limits and ACGIH TLV exposure levels.

**ENVIRONMENTAL CONTROLS:** Not available.

**EYE PROTECTION**: Wear safety glasses with side shields. Have eye wash facilities immediately available.

**SKIN PROTECTION:** Wear chemical resistant gloves if contact is likely.

**RESPIRATORY PROTECTION**: Use NIOSH-approved air-purifying respirator with organic cartridge or canister if exposure cannot be controlled within applicable limits with ventilation.

### **Section 9 - Physical and Chemical Properties**

PHYSICAL STATE: Aerosol - Pressurized Liquid

**COLOR**: See product identification

**ODOR:** Solvent odor

**ODOR THRESHOLD:** Not available.

pH: Not available.

**MELTING POINT**: Not available.

**BOILING POINT:** Not applicable (pressurized mixture) **FLASH POINT:** <-18 degrees C (<-0.4 degrees F), c.c.

**EVAPORATION RATE:** Faster than ether

**FLAMMABILITY:** Not available.

**UPPER/LOWER EXPLOSIVE LIMITS:** Not available.

**VAPOR PRESSURE:** Not established. **VAPOR DENSITY:** Not established.

RELATIVE DENSITY: 0.778
SOLUBILITY: Negligible

PARTITION COEFFICIENT: Not available.

**AUTO-IGNITION TEMPERATURE:** Not available. **DECOMPOSITION TEMPERATURE:** Not available.

VOC PERCENT BY WEIGHT: 43.33
HAPS PERCENT BY WEIGHT: 8.35
MIR NUMBER (EPA AND CA): 1.027

# **Section 10 - Stability and Reactivity**

**STABILITY:** The product is stable under normal conditions.

CONDITIONS TO AVOID: Keep away from heat, sparks, and flames.

Page: 5/6

MILSPRAY Fed-Std 595B #34094 Non-CARC 1K Aerosol Can Revision Date: October 27, 2015

**INCOMPATIBLE MATERIALS:** Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: by fire - Carbon Dioxide and Carbon Monoxide

POSSIBILITY OF HAZARDOUS REACTIONS: Will not occur.

### **Section 11 - Toxicological Information**

LIKELY ROUTES OF EXPOSURE: Skin contact, Inhalation, Eye contact, Ingestion

#### SIGNS AND SYMPTOMS OF EXPOSURE:

**EYE:** Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

**SKIN:** Signs/symptoms may include localized redness, itching, drying and cracking of skin.

**INHALATION:** Intentional concentration and inhalation may be harmful or fatal.

INGESTION: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and

diarrhea.

**CHRONIC EFFECTS:** Not available

TARGET ORGANS: Central nervous system, kidneys, lungs, liver, eyes, skin, brain, respiratory tract, urinary tract,

reproductive system, cardiovascular system

**CANCER INFORMATION:** Not available.

**CARCINOGENICITY:** Not available.

**DEVELOPMENTAL INFORMATION:** Not available.

**MIXTURE TOXICITY:** 

Product Name	LD50 ORAL	LD50 DERMAL	LD50 INHALATION
acetone	N/E	N/E	N/E
propane	1000	1800	N/E
xylene	>3523 mg/kg	>4200 mg/kg	>20 mg/L
n-butane	N/E	N/E	N/E
n-butyl acetate	>10760 mg/kg (rat)	>14112 mg/kg (rabbit)	>21mg/l (rat) 4hr
* ethylbenzene	N/E	N/E	N/E
Carbon black	8000	N/E	N/E
PM acetate	>5000 mg/kg (rat)	>5000 mg/kg (rabbit)	>10.8mg/l (rat) 6hr
ethyl ester	N/E	N/E	N/E
(BIN 14) aliphatic	N/E	N/E	N/E
hydrocarbon			
ethyl acetate	>4934 mg/kg	>20000 mg/kg	>22.5 mg/L
Isobutyl alcohol	N/E	N/E	N/E
n-butyl alcohol	N/E	N/E	N/E
*titanium dioxide	N/E	N/E	N/E
aliphatic petroleum naphtha	N/E	N/E	N/E
Petroleum solvent	N/E	N/E	N/E

<sup>\*</sup>may cause cancer

# **Section 12 - Ecological Information**

**ENVIRONMENTAL EFFECTS:** Not available.

# **Section 13 - Disposal Considerations**

Dispose of container and its contents in accordance with federal, state, and local regulations. Do not puncture,

MILSPRAY Fed-Std 595B #34094 Non-CARC 1K Aerosol Can Revision Date: October 27, 2015

incinerate, or place container in trash compactor.

Section 14 - Transport Information			
	DOT (Ground)	IATA (Air)	IMDG (Water)
UN Number	UN1950	UN1950	UN1950
Transport Hazard Class	2.1	2.1	2.1
Packing Group	N/A	N/A	N/A
UN proper shipping name	Aerosols	Aerosols, Flammable	Aerosols
Hazard Label	Limited Quantity	Limited Quantity	Limited Quantity

No component of this product is a listed Marine Pollutant.

SPECIAL PRECAUTIONS FOR USER: Not available.

## **Section 15 - Regulatory Information**

### **International Chemical Inventory**

All components of this product are listed on or exempt from the following inventories: TSCA (United States), CEPA/DSL (Canada), AICS (Australia), IECSC (China)

#### **SARA Section 313 Toxic Chemicals:**

XYLENE 1330-20-7, \*ETHYLBENZENE 100-41-4, N-BUTYL ALCOHOL 71-36-3

Chemicals listed above are subject to the SARA reporting requirements under 40 CFR 372.45(c)(5).

### California Prop65 Chemicals:

\*ETHYLBENZENE 100-41-4, \*CARBON BLACK 1333-86-4


\*California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

### **Section 16 - Other Information**

HMIS: Health = 2 Flammability = 4 Reactivity = 1 Personal Protection = N/A

NFPA 704: Health = 2 Flammability = 4 Instability = 1



#### DISCLAIMER:

This SDS is based on information believed to be reliable and accurate. Because of changing reporting requirements and other variables it is impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to determine proper personal protection based on the actual condition of use and to comply with all Federal, State and Local laws and regulations.

#### **Revision History**

6/11/2015 – Original SDS version; approval JH

10/27/2015 - Correction of classification and other data