

Safety Data Sheet

MILSPRAY Fed-Std 595B #33446 Desert Tan Non-CARC 1K Touch-Up Pen
Revision Date: June 8, 2015

Contains Custom-Pak U.S. Military FED-STD-595B 33446 Desert Tan

Section 1 - Manufacturer Identification

Product Name: Fed-Std 595B #33446 Desert Tan
Non-CARC 1K Touch-Up Pen



Recommend Use: Touch-Up Military Paint
Supplier's Name: MILSPRAY Military Technologies

Address: 845 Towbin Ave
Lakewood, NJ 08701

Phone: 732-886-2223

EMERGENCY PHONE: 1-800-424-9300 (Chemtrec)

HMIS		NFPA	
Health	2	4	1
Flammability	4	2	1
Reactivity	1		
Personal Protection			

Section 2 - Hazards Identification

GHS Rating:

Flammable Liquids	2
Aspiration Hazard	1
Acute Toxicity – Dermal	4
Skin Corrosion/Irritation	2
Serious Eye Damage/Irritation	2A
Acute Toxicity – Inhalation	4
Specific Target Organ Toxicity Single Exposure	3
Germ Cell Mutagenicity	1A,1B
Carcinogenicity	1A,1B



GHS Signal Word: Danger

GHS Hazards:

- Highly flammable liquid and vapor.
- May be fatal if swallowed and enters airways.
- Harmful in contact with skin.
- Causes skin irritation.
- Causes serious eye irritation.
- Harmful if inhaled.
- May cause drowsiness or dizziness.
- May cause genetic defects.
- May cause cancer.

GHS Precautions:

- Keep out of reach of children.
- Obtain special instructions before use.
- Do not handle until all safety precautions have been read and understood.
- Keep away from heat/sparks/ignition sources. No smoking.
- Keep container tightly closed when not in use.
- Avoid breathing vapor.
- Wash hands thoroughly after handling.
- Use only outdoors or in a well-ventilated area.
- Wear eye protection.
- IF SWALLOWED: Immediately call a POISON CENTER/doctor.
- IF ON SKIN: Wash with plenty of soap and water.

Safety Data Sheet

MILSPRAY Fed-Std 595B #33446 Desert Tan Non-CARC 1K Touch-Up Pen
Revision Date: June 8, 2015

IF INHALED: Remove victim to fresh air and keep comfortable for breathing.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Call a POISON CENTER or doctor if you feel unwell.
Do NOT induce vomiting.
If eye irritation persists: Get medical attention.
In case of fire: Use alcohol resistant foam, carbon dioxide, or dry chemical extinguishing agent to extinguish.
Store in a well-ventilated place. Keep container tightly closed when not in use.
Store in a well-ventilated place. Keep cool.
Dispose of contents/container in accordance with local/regional/national regulations.

Section 3 - Composition/Information on Ingredients

Product Name	CAS #	% by weight
xylene	1330-20-7	13.1
solvent naphtha	64742-95-6	20
* titanium dioxide	13463-67-7	4.8
* ethylbenzene	100-41-4	2.8
PM acetate	108-65-6	0.6
n-butyl acetate	123-86-4	0.6
ethyl acetate	141-78-6	0.4
aliphatic petroleum naphtha	64742-48-9	0.2
(bin 14) aliphatic hydrocarbon	8052-41-3	0.2

Section 4 - First Aid Measures

EYE CONTACT: If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

INHALATION: If inhaled: Move person to fresh air and keep in comfortable position for breathing. If breathing difficulty persists: Get medical advice/attention.

SKIN CONTACT: If on skin: Wash with plenty of soap and water. Remove contaminated clothing and wash before reuse. If skin irritation persists: Get medical advice/attention.

INGESTION: If swallowed: Immediately call a poison center/doctor. Do NOT induce vomiting unless directed to do so by medical personnel.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

See Section 11: Toxicological Information and effects.

Notes to physician: Not available.

Specific treatments: treat symptomatically.

Protection of first-aiders: Not available.

Section 5 - Fire Fighting Measures

SUITABLE EXTINGUISHING MEDIA: CO2 (Carbon Dioxide), dry chemical, or water fog.

UNSUITABLE EXTINGUISHING MEDIA: Water spray may be unsuitable. However, if water is used, fog nozzles

Safety Data Sheet

MILSPRAY Fed-Std 595B #33446 Desert Tan Non-CARC 1K Touch-Up Pen
Revision Date: June 8, 2015

are preferable. Water may be used to cool closed containers to prevent pressure build-up.

SPECIFIC HAZARDS ARISING FROM CHEMICAL: Closed containers exposed to heat from fire may build pressure and explode. Products of combustion may include but are not limited to: oxides of carbon.

PRODUCTS OF COMBUSTION: Not available.

PRODUCTS OF DECOMPOSITION: Not available.

FIRE FIGHTING PROCEDURES: Not available.

SPECIAL PROTECTIVE EQUIPMENT FOR FIRE-FIGHTERS: Full protective equipment including self-contained breathing apparatus should be used.

Section 6 - Accidental Release Measures

PERSONAL PRECAUTIONS: Use personal protection recommended in Section 8.

ENVIRONMENTAL PRECAUTIONS: Prevent contamination of soil/ground, waterways, drains, and sewers.

METHODS OF CONTAINMENT: Absorb spilled liquid in suitable material.

EMERGENCY RESPONDERS: Not available.

NON-EMERGENCY PERSONNEL: Not available.

METHODS OF CLEAN-UP: Use spark-proof tools to sweep or scrape up, containerize, and dispose of properly.

OTHER INFORMATION: Ensure adequate ventilation.

Section 7 - Handling and Storage

HANDLING: Vapors may ignite explosively. Prevent buildup of vapors. Keep from sparks, heat, flame or other heat sources. Do not smoke. Turn off pilot lights, heaters, electric motors and other sources of ignition during use and until all vapors are gone. Do not puncture or incinerate/burn container. Keep container tightly closed while not in use.

STORAGE: Store in dry, well-ventilated area and in accordance with federal, state, and local regulations. Do not expose to heat or store at temperatures above 50 degrees C / 122 degrees F. If storing in cold temperatures, allow product to warm to room temperature before use. Keep container tightly closed and away from heat and sunlight when not in use.

Section 8 - Exposure Controls/Personal Protection

Product Name	ACGIH TLV-STEL	ACGIH TLV-TWA	OSHA PEL-TWA
xylene	150ppm	100 ppm	100 ppm
solvent naphtha	N/E	100 ppm	100 ppm
* titanium dioxide	N/E	10 mg/m3 ppm	15 mg/m3 ppm
* ethylbenzene	125 ppm	100 ppm	100 ppm
PM acetate	N/E	N/E	N/E
n-butyl acetate	200 ppm	150 ppm	150 ppm
ethyl acetate	N/E	400 ppm	400 ppm
aliphatic petroleum naphtha	N/E	100 ppm	500ppm
(bin 14) aliphatic hydrocarbon	N/E	N/E	N/E

ENGINEERING CONTROLS: Provide adequate ventilation to keep air contamination below OSHA permissible exposure limits and ACGIH TLV exposure levels.

ENVIRONMENTAL CONTROLS: Not available.

EYE PROTECTION: Wear safety glasses with side shields. Have eye wash facilities immediately available.

SKIN PROTECTION: Wear chemical resistant gloves if contact is likely.

RESPIRATORY PROTECTION: Use NIOSH-approved air-purifying respirator with organic cartridge or canister if

Safety Data Sheet

Page: 4/6

MILSPRAY Fed-Std 595B #33446 Desert Tan Non-CARC 1K Touch-Up Pen
Revision Date: June 8, 2015

exposure cannot be controlled within applicable limits with ventilation.

HYGIENE: Not available.

Section 9 - Physical and Chemical Properties

PHYSICAL STATE: Liquid

COLOR: See product identification

ODOR: Solvent odor

ODOR THRESHOLD: Not available.

pH: Not available.

MELTING POINT: Not available.

BOILING POINT: 75 - 186 degrees C (167 - 367 degrees F)

FLASH POINT: >23 degrees C (>73 degrees F), c.c.

EVAPORATION RATE: slower than ether

FLAMMABILITY: Not available.

UPPER/LOWER EXPLOSIVE LIMITS: Not available.

VAPOR PRESSURE: Not established.

VAPOR DENSITY: Not established.

RELATIVE DENSITY: 1.096

SOLUBILITY: Negligible

PARTITION COEFFICIENT: Not available.

AUTO-IGNITION TEMPERATURE: Not available.

DECOMPOSITION TEMPERATURE: Not available.

VOC PERCENT BY WEIGHT: 55.47

HAPS PERCENT BY WEIGHT: 31.61

Section 10 - Stability and Reactivity

STABILITY: The product is stable under normal conditions.

CONDITIONS TO AVOID: Keep away from heat, sparks, and flames.

INCOMPATIBLE MATERIALS: Strong oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: by fire - Carbon Dioxide and Carbon Monoxide

POSSIBILITY OF HAZARDOUS REACTIONS: Will not occur.

Section 11 - Toxicological Information

LIKELY ROUTES OF EXPOSURE: Skin contact, Inhalation, Eye contact, Ingestion

SIGNS AND SYMPTOMS OF EXPOSURE:

EYE: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

SKIN: Signs/symptoms may include localized redness, itching, drying and cracking of skin.

INHALATION: Intentional concentration and inhalation may be harmful or fatal.

INGESTION: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhea.

Safety Data Sheet

MILSPRAY Fed-Std 595B #33446 Desert Tan Non-CARC 1K Touch-Up Pen
Revision Date: June 8, 2015

CHRONIC EFFECTS: Not available

TARGET ORGANS: Central nervous system, kidneys, lungs, liver, eyes, skin, brain, respiratory tract, urinary tract, reproductive system, cardiovascular system

CANCER INFORMATION: Not available.

CARCINOGENICITY: Not available.

DEVELOPMENTAL INFORMATION: Not available.

MIXTURE TOXICITY:

Product Name	LD50 ORAL	LD50 DERMAL
xylene	4300	2000
solvent naphtha	N/E	N/E
* titanium dioxide	N/E	N/E
* ethylbenzene	3500	5000
PM acetate	8535	5000
n-butyl acetate	10768	17601
ethyl acetate	5620	20 mL/kg
aliphatic petroleum naphtha	N/E	N/E
(bin 14) aliphatic hydrocarbon	N/E	N/E

*may cause cancer

Section 12 - Ecological Information

ENVIRONMENTAL EFFECTS: Not available.

Section 13 - Disposal Considerations

Dispose of container and its contents in accordance with federal, state, and local regulations. Do not puncture, incinerate, or place container in trash compactor.

Section 14 - Transport Information

	DOT (Ground)	IATA (Air)	IMDG (Water)
UN Number	UN1263	UN1263	UN1263
Transport Hazard Class	3	3	3
Packing Group	III	III	III
UN proper shipping name	Paint	Paint	Paint
Hazard Label	Limited Quantity	Limited Quantity	Limited Quantity

SPECIAL NOTE: If containers have <30ml (1 fl. oz.), they may qualify to be shipped an Excepted Quantity, see IMDG 3.5.1 for details. No component of this product is a listed Marine Pollutant (49 CFR 172,101,Appendix B).

SPECIAL PRECAUTIONS FOR USER: Not available.

Section 15 - Regulatory Information

International Chemical Inventory

All components of this product are listed on or exempt from the following inventories: TSCA (United States), CEPA/DSL (Canada), AICS (Australia), IECSC (China)

Safety Data Sheet

MILSPRAY Fed-Std 595B #33446 Desert Tan Non-CARC 1K Touch-Up Pen
Revision Date: June 8, 2015

SARA Section 313 Toxic Chemicals:

XYLENE 1330-20-7, *ETHYLBENZENE 100-41-4

Chemicals listed above are subject to the SARA reporting requirements under 40 CFR 372.45(c)(5).

California Prop65 Chemicals:

*ETHYLBENZENE 100-41-4

*California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

This product contains chemicals known to the state of California to cause cancer and birth defects or other reproductive harm.

Section 16 - Other Information

HMIS: Health = 2 Flammability = 4 Reactivity = 1 Personal Protection = N/A

NFPA 704: Health = 2 Flammability = 4 Instability = 1

HMIS	
Health	2
Flammability	4
Reactivity	1
Personal Protection	



DISCLAIMER:

This SDS is based on information believed to be reliable and accurate. Because of changing reporting requirements and other variables it is impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to determine proper personal protection based on the actual condition of use and to comply with all Federal, State and Local laws and regulations.

Revision History

6/08/2015 – Original SDS version; approval JH
9/30/2015 – Correction of Product ID information