

Safety Data Sheet

MILSPRAY MIL-DTL-53022E-Type II-Component B - Catalyst
Revision Date: May 28, 2015

Contains NCP Coatings DynaSpec Catalyst Component MIL-DTL-53022E Type II

Section 1 - Manufacturer Identification

Product Name: MIL-DTL-53022E Type II
Component B - Catalyst

Recommend Use: Touch-Up Military Paint

Supplier's Name: MILSPRAY Military
Technologies

Address: 845 Towbin Ave
Lakewood, NJ 08701


Phone: 732-886-2223

EMERGENCY PHONE: 1-800-424-9300 (Chemtrec)

MILSPRAY

Military Technologies

HMIS	
Health	2
Flammability	3
Physical Hazard	0
Personal Protection	G



Section 2 - Hazards Identification

GHS Ratings:

Skin Irritant	2
Eye Irritant	2
Flammable Liquid	3

GHS Signal Word: Danger

GHS Hazards:

- Highly flammable liquid and vapor.
- Harmful if swallowed.
- Causes skin irritation.
- Causes serious eye irritation.
- Harmful if inhaled.
- May cause respiratory irritation.
- May cause drowsiness or dizziness.



GHS Precautions

IF SWALLOWED: Immediately call a POISON CENTER or doctor.

IF ON SKIN: Wash with plenty of soap and water.

IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

If skin irritation or rash occurs: Get medical attention.

If experiencing respiratory symptoms: Get medical attention.

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground container and receiving equipment. Use explosion-proof equipment.

Avoid breathing fume/mist/vapors/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area. In case of inadequate ventilation wear respiratory protection. Wear protective gloves, clothing, eye protection/face protection. Wash contaminated clothing before reuse.

Dispose of contents/container in accordance with local/national/international regulations.

In case of fire: Use appropriate method to extinguish. See Section 5 of SDS.

Store in a cool, well-ventilated place. Keep container tightly closed.

Safety Data Sheet

MILSPRAY MIL-DTL-53022E-Type II-Component B - Catalyst

Revision Date: May 28, 2015

Section 3 - Composition/Information on Ingredients

Chemical	CAS No.	Weight	GHS
*4-Methyl-2-pentanone	108-10-1	33.43	H225 Highly flammable liquid and vapor. H319 Causes serious eye irritation. H332 Harmful if inhaled. H336 May cause respiratory irritation.
Bisphenol A Diglycidyl Ether	25036-25-3	20-25%	H317 May cause an allergic skin reaction.
*1-Butanol	71-36-3	17.09	H226 Flammable liquid and vapor. H302 Harmful if swallowed H315 Causes skin irritation. H318 Causes serious eye damage. H332 Harmful if inhaled. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.
1-Methoxy-2-Propanol	107-98-2	10-15%	H226 Flammable liquid and vapor. H332 Harmful if inhaled. H336 May cause drowsiness or dizziness. H360 May Damage fertility or the unborn child.

Safety Data Sheet

MILSPRAY MIL-DTL-53022E-Type II-Component B - Catalyst

Revision Date: May 28, 2015

Ethyleneamine Mixture	111-40-0	5-10%	H319 Causes serious eye irritation. H371 May cause damage to organs. H373 May cause damage to organs through prolonged or repeated exposure. Toxic if inhaled.
*Mixed Xylenes	1330-20-7	5.58	H226 Flammable liquid and vapor. H315 Causes skin irritation H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure.
Ethyl Benzene	100-41-4	0.95%	H225 Flammable liquid and vapor. H315 Causes skin irritation. H319 Causes serious eye irritation. H332 Harmful if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H373 May cause damage to organs through prolonged or repeated exposure.

* Toxic chemical subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

"WARNING: THIS PRODUCT MAY CONTAIN CHEMICALS KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM."

Section 4 - First Aid Measures

EYE CONTACT: Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention

Safety Data Sheet

Page: 4/9

MILSPRAY MIL-DTL-53022E-Type II-Component B - Catalyst

Revision Date: May 28, 2015

promptly.

SKIN CONTACT: Wash with soap and water. Get medical attention if irritation develops or persists. Remove contaminated shoes and clothes and clean before reuse.

INHALATION: Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention.

INGESTION: DO NOT induce vomiting. Get medical attention immediately.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED:

SYMPTOMS: Severe eye, skin, and respiratory irritant.

EFFECTS: Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin, and/or eyes.

Section 5 - Fire Fighting Measures

FLASH POINT: 74°F(23°C) SETAFLASH CLOSED CUP

SUITABLE EXTINGUISHING MEDIA: Water mist or fog, dry chemical, foam, carbon dioxide.

UNSUITABLE EXTINGUISHING MEDIA: Not available.

UNUSUAL FIRE & EXPLOSION HAZARDS: Flammable liquid and vapor. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, grind or expose such containers to heat, flame, sparks, static electricity, or other sources of ignition. Also, do not reuse container without commercial cleaning or reconditioning.

PRODUCTS OF COMBUSTION: During combustion toxic vapors may be released. Under fire conditions, corrosive fumes and toxic vapors may be emitted.

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear. Use water with caution. Material will float and may ignite on surface of water. Water may be ineffective in fighting the fire. Water spray to cool containers or protect personnel. Use with caution. Water runoff can cause environmental damage. Dike collect water used to fight fire. Small fires: carbon dioxide or dry chemical. Large fire: alcohol-type aqueous film-forming foam or water spray.

NFPA 704: Health = 2 Flammability = 3 Instability = 0

Section 6 - Accidental Release Measures

PERSONAL PRECAUTIONS: Not available.

ENVIRONMENTAL PRECAUTIONS: Avoid runoff into storm sewers and ditches which lead to waterways.

METHODS OF CONTAINMENT: Dike spill area and absorb the spilled liquid with earth, sawdust or a commercially available absorbent..

METHODS OF CLEAN-UP:

SMALL SPILLS: Eliminate all sources of ignition. Provide good ventilation and minimize the breathing of vapors and avoid skin contact. Dike spill area and absorb the spilled liquid with earth, sawdust or a commercially available absorbent. Shovel spent absorbent into recovery or salvage drums for appropriate disposal.

LARGE SPILLS: Wear appropriate personal protective equipment. Eliminate all ignition sources. Prevent additional discharge of material if able to do so safely. Do not touch or walk through spilled material. Avoid runoff into storm sewers and ditches which lead to waterways. Ventilate spill area. Stay upwind of spill. Use only non-combustible material for cleanup. Use clean, non-sparking tools to collect absorbed materials. Absorb spill with inert material

Safety Data Sheet

MILSPRAY MIL-DTL-53022E-Type II-Component B - Catalyst

Revision Date: May 28, 2015

(e.g. dry sand, earth or sawdust), then place in a chemical waste collector.

OTHER INFORMATION: EMERGENCY PRECAUTIONS: Eliminate ignition sources. Avoid large exposures to vapors.

Section 7 - Handling and Storage

HANDLING: Use only in a well ventilated area. Avoid breathing vapor, fumes, or mist. Avoid contact with eyes, skin, and clothing. Ground and bond containers when transferring material. Use spark-proof tools and explosion proof equipment. Always open containers slowly to allow any excess pressure to vent. Follow all SDS/label precautions even after containers are emptied because they may retain product residues.

STORAGE: Keep away from heat, sparks, and flame. Store containers in a cool, well ventilated place. Keep container closed when not in use.

Section 8 - Exposure Controls/Personal Protection

Chemical	OSHA Exposure Limits	ACGIH Exposure Limits
*4-Methyl-2-pentanone	PEL 50 PPM TWA	TLV 50 PPM TWA
Bisphenol A Diglycidyl Ether	PEL: 15 mg/m ³ TWA	TLV: 10 mg/m ³ TWA
*1-Butanol	PEL 50ppm TWA	TLV 50ppm TWA
1-Methoxy-2-Propanol	PEL 100 PPM TWA	TLV 100 PPM TWA
Ethyleneamine Mixture	PEL 1ppm TWA	TLV 1ppm TWA
*Mixed Xylenes	PEL 100 PPM TWA	TLV 100 PPM TWA
Ethyl Benzene	PEL 100 PPM TWA	TLV 100 PPM TWA

NE= Not Established

ENGINEERING CONTROLS: Engineering controls should be in place to minimize exposure to vapors and any ignition sources.

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

SKIN PROTECTION: Wear impervious gloves to prevent contact with skin. Wear protective gear as needed - apron, suit, boots.

RESPIRATORY PROTECTION: NIOSH/MSHA approved respirators may be necessary if airborne concentrations are expected to exceed exposure limits.

HYGIENE: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

OTHER USE PRECAUTIONS : Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

Safety Data Sheet

Page: 6/9

MILSPRAY MIL-DTL-53022E-Type II-Component B - Catalyst

Revision Date: May 28, 2015

Section 9 - Physical and Chemical Properties

PHYSICAL STATE: Liquid

ODOR: Typical

ODOR THRESHOLD: Not determined.

pH: Not determined.

BOILING POINT: 237.0 F

FLASH POINT: 74°F (23°C) SETAFLASH CLOSED CUP

FLAMMABILITY LIMITS: 0.8 to 16.1

VAPOR PRESSURE: Not determined.

VAPOR DENSITY: Heavier than air.

SPECIFIC GRAVITY: 0.9016230

AUTO-IGNITION TEMPERATURE: Not determined.

VOC EPA METHOD 24: 5.1499748 lb/gal

Section 10 - Stability and Reactivity

STABILITY: No information available.

CONDITIONS TO AVOID: Avoid impact, friction, heat, sparks, flame and source of ignition.

INCOMPATIBLE MATERIALS: Prevent contact with reactive metals, acids, peroxides, and strong oxidizing agents..

HAZARDOUS DECOMPOSITION PRODUCTS: During thermal decomposition, toxic gasses, corrosive gasses, and nitrogen oxides may be formed.

POSSIBILITY OF HAZARDOUS REACTIONS: No information available.

Section 11 - Toxicological Information

LIKELY ROUTES OF EXPOSURE: Eye contact, Skin contact, Ingestion, and Inhalation

EYE: Causes severe eye irritation.

SKIN: Causes skin irritation. Prolonged or repeated contact can result in defatting and drying of the skin which may result in skin irritation and dermatitis (rash).

INHALATION: Vapors are irritating to nasal passages and throat. High concentrations can cause stupor and headaches. May cause dizziness and drowsiness.

INGESTION: Irritating to mouth, throat, and stomach. May cause headache. May cause dizziness and drowsiness and/or stupor.

CHRONIC EFFECTS: Significant exposure to this chemical may adversely affect people with chronic disease of the respiratory system, central nervous system, kidney, liver, skin, and/or eyes.

TARGET ORGANS: Not available.

CANCER INFORMATION: Not available.

CARCINOGENICITY: Not available.

Safety Data Sheet

MILSPRAY MIL-DTL-53022E-Type II-Component B - Catalyst

Revision Date: May 28, 2015

DEVELOPMENTAL INFORMATION: Not available.**MIXTURE TOXICITY:** Not available.**ACUTE TOXICITY VALUES:** The acute effects of this product have not been tested. Data on individual components are listed below.

CAS Number	Test
108-10-1	Oral LD50:>2080 mg/kg Dermal LD50:>2000mg/kg Vapor LC50:16.4mg/l
25036-25-3	Oral: Rat LD50: > 2.000 mg/kg Dermal: Rat LD50: > 2,000mg/kg,
71-36-3	Oral LD50:>790 mg/kg Dermal LD50:>3400mg/kg Vapor LC50:20mg/l
107-98-2	Oral LD50:>4016mg.kg Dermal LD50:>2000mg/kg Vapor LC50:>27.596mg/l
111-40-0	Oral LD50:>12565mg/kg Dermal LD50:>13330mg/kg Vapor LC50:>4.4mg/l
1330-20-7	Oral LD50:>3523mg.kg Dermal LD50:>4200mg/kg Vapor LC50:>20mg/l
100-41-4	Oral LD50:3500mg/kg Dermal LD50:15433mg/kg Vapor LC50:>20mg/l

Section 12 - Ecological Information

ENVIRONMENTAL EFFECTS: Information not available on mixture. Information on individual components is listed below if available.

CAS Number	Test
108-10-1	No information available.
25036-25-3	No information available.
71-36-3	No information available.
107-98-2	No information available.

Safety Data Sheet

MILSPRAY MIL-DTL-53022E-Type II-Component B - Catalyst
Revision Date: May 28, 2015

111-40-0	No information available.
1330-20-7	No information available.
100-41-4	No information available.

Section 13 - Disposal Considerations

Dispose of waste in accordance with all local, state, and federal regulations.

Section 14 - Transport Information

DOMESTIC (USDOT):

Proper Shipping Name: Paint Related Material
Hazard Class: 3
Packing Group: III
Quantity: Not applicable.
UN Number: 1263

Section 15 - Regulatory Information

REGULATORY OVERVIEW: The regulatory data in section 15 is not intended to be all-inclusive, only selected regulations are represented.

TSCA: All components of this material are either listed or exempt from listing on the TSCA Inventory.

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312/313 REPORTABLE INGREDIENTS: See Section 3.

EPA HAZARDS:

FIRE: Yes

PRESSURE GENERATING: No

REACTIVITY: No

ACUTE: Yes

CHRONIC: Yes

DSL: All components of this material are on or exempt from listing on the Canadian Domestic Substances List (DSL).

Section 16 - Other Information

HMIS: Health = 2 Flammability = 3 Reactivity = 0 Personal Protection = G

NFPA 704: Health = 2 Flammability = 3 Instability = 0

DISCLAIMER:

This SDS is based on information believed to be reliable and accurate. Because of

Safety Data Sheet

Page: 9/9

MILSPRAY MIL-DTL-53022E-Type II-Component B - Catalyst

Revision Date: May 28, 2015

changing reporting requirements and other variables it is impossible to guarantee the accuracy of the information contained in this document. It is the responsibility of the user to determine proper personal protection based on the actual condition of use and to comply with all Federal, State and Local laws and regulations.

Revision History

6/23/2015 - Original SDS version; approval JH